



SIZE		ID	L	H	W	H1	H2	K1	K2	d1	d2	F
DN	NPS											
15	1/2"	12	71	71	145	8.5	37	36	42	6	6	9
20	3/4"	15	81	74	145	14	40	36	42	6	6	9
25	1"	17	90	83	155	13	46	42	50	6	7	11
32	1-1/4"	25	125	94	155	11	57	42	50	6	7	11
40	1-1/2"	32	138	113	196	18.5	70	50	70	7	9	14
50	2"	38	152	120	196	18.5	77	50	70	7	9	14
65	2-1/2"	50	200		230		95	70	102	9	11	17
80	3"	65	240		260		108	70	102	9	11	17

NO.	Component Name	Material		
		CF8M	CF8	WCB
1	Body	CF8M	CF8	WCB
2	Bonnet	CF8M	CF8	WCB
3	Seat	PTFE	PTFE	PTFE
4	Ball	SS316	SS304	SS304
5	Stem	SS316	SS304	SS304
6	Thrust Washer	PTFE	PTFE	PTFE
7	Packing	PTFE	PTFE	PTFE
8	Packing Gland	SS202	SS202	SS202
9	Hex Nut	SS202	SS202	SS202
10	Handle	SS202	SS202	SS202
11	Lock	SS202	SS202	SS202

Nominal Pressure	1000	Psi
Test Pressure	Strength Test	10.4
	Seal Test	7.6
	Air Seal Test	0.6
Working Temperature	-20°C --190°C	
Applicable Media: Water, Steam, Oil, Acetic Acid		

Features:

1. Design & Manufacture: ASTM B16.34
2. Test & Inspection: API598
3. Direct Drive Actuator Mounted Device Standard: ISO5211
4. Lockable Device Available Or Actuator Drive

1000WOG 3-WAY BALL VALVE